BOMAG TANDEM VIBRATORY ROLLERS BW-AD/SL BW-80AD-2 KUBOTA D722B



(1995-2011)

(1995-2011)		
ENGINE Kubota D722		
Capacity: 3,9 liter		
Name at the facilities and the second		CLIMATE
Normal, fuel sulfur level <0,5 %		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 250) hours/ 12 months	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 250) hours/ 12 months	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 250) hours/ 12 months	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
——————————————————————————————————————) hours/ 12 months	
) hours/ 12 months	CLIMATE
USE) hours/ 12 months	сымате Tropical
use Initial service) hours/ 12 months	
use Initial service PRODUCT RECOMMENDATION 1) hours/ 12 months	
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30) hours/ 12 months	
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours) hours/ 12 months	
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE) hours/ 12 months	Tropical
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service) hours/ 12 months	Tropical
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1) hours/ 12 months	Tropical
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20) hours/ 12 months	Tropical
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours	D hours/ 12 months	Tropical
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours) hours/ 12 months	Tropical CLIMATE Mediterranean
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE Initial service	PRODUCT RECOMMENDATION 2	CLIMATE Mediterranean CLIMATE
Check every 10 hours, change every 250 use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours use Initial service PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30		CLIMATE Mediterranean CLIMATE Moderate

BOMAG TANDEM VIBRATORY ROLLERS BW-AD/SL BW-80AD-2 KUBOTA D722B



(1995-2011)

USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

HYDRAULIC SYSTEM Capacity: 9 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus H 32	Perlus AF 32			
Check every 10 hours, change eve	ry 2000 hours/ 24 months			

COOLING SYSTEM Capacity: 1,9 liter				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF		

Check every 10 hours, change every 2000 hours/24 months

ARTICULATED JOINT				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.