

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-145PDH-3 DEUTZ BF4L 2011 (S/N S/N 101 581 22 ->/ 901 581 48 ->)



ENGINE Deutz BF4L-1011
Capacity: 10,5 liter

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40

Change every 50 hours

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL
Capacity: 6,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Change every 50 hours

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-145PDH-3 DEUTZ BF4L 2011 (S/N S/N 101 581 22 ->/ 901 581 48 ->)

**HUB REDUCTIONS**

Capacity: 1 liter (each nub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Change every 50 hours***HYDRAULIC SYSTEM**

Capacity: 44 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

*Check every 10 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-145PDH-3 DEUTZ BF4L 2011 (S/N S/N 101 581 22 ->/ 901 581 48 ->)

**VIBRATORY BEARINGS**

Capacity: 2,1 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.