

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-216PDH-4 (2010 AND AFTER)



ENGINE Deutz TCD 2012 L06 2V
Capacity: 12,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

DIFFERENTIAL REAR
Capacity: 11 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

HUB REDUCTIONS REAR
Capacity: 2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

TRANSMISSION
Capacity: 1,9 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

HYDRAULIC SYSTEM
Capacity: 60 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-216PDH-4 (2010 AND AFTER)

**COOLING SYSTEM**

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

REDUCTION UNIT DRUM DRIVE

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

VIBRATORY BEARINGS

Capacity: 0,8 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.