

# CASE TRACKED EXCAVATORS CX CX700B

## ISUZU AH-6WG1XYSS, (2008-2014)



**ENGINE** Isuzu AH-6WG1X  
Capacity: 52 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

### HYDRAULIC SYSTEM

Capacity: 310 liter (Hydraulic tank), Capacity: 650 liter (System)

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       |          |

### GREASE POINTS/NIPPLES

| USE                             |                                | CLIMATE                         |
|---------------------------------|--------------------------------|---------------------------------|
| Normal                          |                                | Moderate                        |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2       | PRODUCT RECOMMENDATION 3        |
| <b>Q7 MP Calcep Grease WR 2</b> | <b>Caliplex HD Grease EP 2</b> | <b>Q5 MP Calcep Grease EP 2</b> |

### COOLING SYSTEM

Capacity: 108 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

### SWING REDUCTION UNIT

Capacity: 13,5 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

# CASE TRACKED EXCAVATORS CX CX700B

## ISUZU AH-6WG1XYSS, (2008-2014)

**TRAVEL REDUCTION UNIT**

Capacity: 15 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*