CASE WHEELED LOADERS 121D PERKINS 704.30 (2002-2005)



Normal PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Moderate PRODUCT RECOMMENDATION 3
	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT AND REAR Capacity: 3,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 12 months	

HUB REDUCTIONS Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change every 1000 hour	rs/ 12 months

TRANSFERBOX (4x4) Capacity: 3,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours/ 12 months	

TRANSMISSION HYDROSTATIC Capacity: 0-0 liter (Combined with I		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Change every 36 months/ 3000 ho	urs	

CASE WHEELED LOADERS 121D PERKINS 704.30 (2002-2005)



HYDRAULIC SYSTEM Capacity: 40 liter (Hydraulic tank), Capacit	y: 65 liter (Total)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 36 months/ 3000 hours

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Change every 50 hours	

COOLING SYSTEM Capacity: 15,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.