

CASE WHEELED LOADERS 921C CUMMINS QSM11 (1999-2008)



ENGINE Cummins QSM11
Capacity: 36,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

DIFFERENTIAL FRONT
Capacity: 36,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR
Capacity: 36,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS
Capacity: 13,6 liter (each hub)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4/3
Capacity: 28,4 liter (Change capacity), Capacity: 46 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 50 hours, change every 1000 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 50 hours, change every 100 hours

HYDRAULIC SYSTEM
Capacity: 125 liter (Hydraulic tank), Capacity: 242 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 50 hours, change every 2000 hours

CASE WHEELED LOADERS 921C CUMMINS QSM11 (1999-2008)

**COOLING SYSTEM**

Capacity: 57 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.