

# CASE SKID STEER LOADERS SR150 (2012-2014)



**ENGINE** Shibaura ISM N844LT  
Capacity: 7,5 liter

| USE                           |                           | CLIMATE                             |
|-------------------------------|---------------------------|-------------------------------------|
| Normal                        |                           | Moderate                            |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3            |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

*Check every 10 hours, change every 250 hours*

| USE                           |                           | CLIMATE                             |
|-------------------------------|---------------------------|-------------------------------------|
| Initial service               |                           | Moderate                            |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3            |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

*Change every 50 hours*

**CHAIN DRIVE UNIT**  
Capacity: 6,25 liter (each)

| USE                         |                           | CLIMATE                             |
|-----------------------------|---------------------------|-------------------------------------|
| Normal                      |                           | Moderate                            |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3            |
| <b>Kroontrak MTH 10W-30</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

*Check every 500 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 15 liter (Hydraulic tank), Capacity: 25,5 liter (System)

| USE                         |                           | CLIMATE                             |
|-----------------------------|---------------------------|-------------------------------------|
| Normal                      |                           | Moderate                            |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3            |
| <b>Kroontrak MTH 10W-30</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

*Check every 10 hours, change every 1000 hours*

## GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

*Change every 10 hours*

# CASE SKID STEER LOADERS SR150 (2012-2014)



## COOLING SYSTEM

Capacity: 15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

*Check every 10 hours, change every 1000 hours*

## TRAVEL REDUCTION UNIT

Capacity: 1 liter (each)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 500 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*