

CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)

**ENGINE** FPT F4HE9484C

Capacity: 12,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Check every 10 hours, change every 500 hours/ 6 months***DIFFERENTIAL FRONT**

Capacity: 10,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 250 hours, change every 1000 hours/ 12 months***DIFFERENTIAL REAR**

Capacity: 10,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 250 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 250 hours, change every 1000 hours/ 12 months***TRANSMISSION POWERSHIFT 4/2**

Capacity: 14 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Check every 250 hours, change every 1000 hours/ 12 months*

CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)



TRANSMISSION POWERSHUTTLE 4/4

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 118 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

GREASE POINTS/NIPPLES TELESCOPIC BOOM

We are unable to give a standard recommendation for this component. Please contact our service department.

CASE BACKHOE LOADERS 695 SUPER R (4WS) FPT F4HE9484C (2008-2020)



COOLING SYSTEM

Capacity: 24 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.