PRODUCT RECOMMENDATION

CATERPILLAR ASPHALT PAVERS AP/BG AP-1000B AGP, 7HN

ENGINE
Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Change every 250 hours/ 1 months		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Synfleet SHPD 10W-40	**Multifleet SHPD 10W-40**	
Change every 250 hours/ 1 months		

HUB REDUCTIONS
Capacity: 5 liter (each hub)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 500 hours/ 3 months		

HYDRAULIC SYSTEM
Capacity: 189 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours/ 12 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Agridiesel CRD+ 15W-40**	**Agrifluid HT-Plus**
Change every 1000 hours/ 12 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR ASPHALT PAVERS AP/BG AP-1000B AGP, 7HN

COOLING SYSTEM
Capacity: 37 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 6000 hours/ 72 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Change every 24 months/ 3000 hours

PUMP DRIVE UNIT
Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours/ 12 months

REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S)
Capacity: 0,65-1 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 500 hours/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367