

USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet MSP 15W-40	
Check every 10 hours, change every 3	months/ 500 hours	
use Preferred		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP Ultra 10W-40
Check every 10 hours, change every 3	months/ 500 hours	
use Normal		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
Check every 10 hours, change every 3	months/ 500 hours	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	
Check every 10 hours, change every 3	months/ 500 hours	
use Alternative (acceptable)		climate Mediterranean
PRODUCT RECOMMENDATION 1 Dieselfleet MSP 15W-40		
Check every 10 hours, change every 3	months/ 500 hours	
use Alternative (acceptable)		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel MSP 15W-40



FINAL DRIVES Capacity: 15 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

TRANSMISSION HYDROSTATIC			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 500 hours, change every 12 months/ 2000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
	16		

Check over 500 hours change every 12 months / 2000 hours		
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Check every 500 hours, change every 12 months/ 2000 hours

HYDRAULIC SYSTEM Capacity: 80 liter (System), Capacity: 58 liter (Tank)			
USE	CLIMATE		
Normal	Mediterranean		
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			

Check every 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 500 hours, change every 12 months/ 2000 hours		

Check every 500 hours, change every 12 months/ 2000 hours



COOLING SYSTEM Capacity: 7,5 liter (Radiator), Capacity: 25 liter (System)		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 12000 hours/ 72 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 500 hours		

TRACK PINS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 50 hours		

Check every 50 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Check every 50 hours		·

TRACK ROLLERS & IDLERS

We are unable to give a standard recommendation for this component. Please contact our service department.



WINCH Capacity: 4,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.