# CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)



ENGINE C27 Acert Capacity: 95 liter			
USE		CLIMATE	
Preferred		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40		
Check every 10 hours, change every 3 m	oonths/ 500 hours		
USE		CLIMATE	
Preferred		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	
Check every 10 hours, change every 3 m	oonths/ 500 hours		
USE		CLIMATE	
Alternative (acceptable)		Mediterranean	
PRODUCT RECOMMENDATION 1			
Dieselfleet MSP 15W-40			
Check every 10 hours, change every 3 m	oonths/ 500 hours		
USE		CLIMATE	
Alternative (acceptable)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	
Check every 10 hours, change every 3 m	oonths/ 500 hours		
USE		CLIMATE	
Acceptable		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 3 m	oonths/ 500 hours		
USE		CLIMATE	
Acceptable		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40		
Check every 10 hours, change every 3 m	oonths/ 500 hours		

#### **DIFFERENTIAL REAR** Capacity: 151 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)



TRANSMISSION + TORQUE CONVERTE Capacity: 61 liter (Complete)	R	
USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 6 mo	nths/ 1000 hours	
USE		CLIMATE
Flexible (max)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Charle avery 10 hours shange avery 6 me	nthe/ 1000 hours	

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM HOIST + BRAKE Capacity: 130 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 months/ 1000 hours		

### CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

#### FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
USE	CLIMATE
Light Duty	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

## CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)



### WHEEL BEARINGS FRONT

Capacity: 3,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 174 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
	1. 1.0000.1	

Check every 10 hours, change every 36 months/ 6000 hours

POWER STEERING HYDRAULIC SYSTEM Capacity: 38 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check even 40 hours checker over 6 menths/4000 hours		

Check every 10 hours, change every 6 months/ 1000 hours

Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 10 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.