## CATERPILLAR FORKLIFT TRUCKS, DIESEL DP50 MITSUBISHI S6E2 (1992-1999)



ENGINE Mitsubishi S6E2	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
HDX 30	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
HDX 20W-20	
Change every 1 months/ 200 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
HDX 10W	
Change every 1 months/ 200 hours	
TRANSMISSION Powershift	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	

## ATF Dexron II-D

Change every 6 months/ 1200 hours

## CATERPILLAR FORKLIFT TRUCKS, DIESEL DP50 MITSUBISHI S6E2 (1992-1999)



HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 12 months/ 2400 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		
Character average 12 magnetics (2400 hours	5	

Change every 12 months/ 2400 hours

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 12 months/ 2400 hours		

GREASE POINTS/NIPPLES CHASSIS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## CATERPILLAR FORKLIFT TRUCKS, DIESEL DP50 MITSUBISHI S6E2 (1992-1999)



DRIVE GEARS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 6 months/ 1200 hours		· ·
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Change every 6 months/ 1200 hours		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.