

# CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)

**ENGINE (LPG) Mitsubishi 4G63**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |  |
|-----------------------------|-------------------------------|--|
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 15W-40</b> |  |

*Change every 1 months/ 200 hours*

**DIFFERENTIAL AND FINAL DRIVES FRONT**

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

**TORQUE CONVERTER**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>ATF Dexron II-D</b>   |  |  |

*Change every 6 months/ 1200 hours*

**TRANSMISSION Powershift**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>ATF-A</b>             |  |  |

# CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)



## HYDRAULIC SYSTEM

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 12 months/ 2400 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Perlus H 22***Change every 12 months/ 2400 hours*

## HYDRAULIC BRAKE SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 12 months/ 2400 hours*

## GREASE POINTS/NIPPLES CHASSIS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Grease EP 1**

## GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)



## DRIVE GEARS

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 6 months/ 1200 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

*Change every 6 months/ 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*