CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GP35 MITSUBISHI 4G64



(1992-1999)

ENGINE (PETROL) Mitsubishi 4G6	4	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 15W-40	
Change every 1 months/200 hours	<u>'</u>	'

Change every 1 months/ 200 hours

DIFFERENTIAL		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 6 months/ 1200 hour	s	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Change every 6 months/ 1200 hour	S	

TRANSFERBOX		
use Normal		climate Mediterranean
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 6 months/ 1200 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Change every 6 months/ 1200 hours

Agrifluid HT-Plus

TRANSMISSION Powershift		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 6 months/ 1200 hours		

SP Gear 5015

Gearlube GL-4 80W

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GP35 MITSUBISHI 4G64



(1992-1999)

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 12 months/ 2400 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Perlus H 22	
Change every 12 months/ 2400 hours	

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Change every 12 months/ 2400 hours	1	1	

GREASE POINTS/NIPPLES CHASSIS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

GREASE POINTS/NIPPLES WHEEL BEARINGS		
use Normal		сымате Moderate
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.