

CATERPILLAR TRACKED EXCAVATORS

245D 7ZJ (1992-1993)



ENGINE 3406C
Capacity: 46,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	Multifleet SCD 30

Change every 250 hours/ 1 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 250 hours/ 1 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Change every 250 hours/ 1 months

FINAL DRIVES
Capacity: 60,5 liter (each side)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 1 months/ 250 hours

CATERPILLAR TRACKED EXCAVATORS

245D 7ZJ (1992-1993)



HYDRAULIC SYSTEM

Capacity: 403 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 77,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 24 months/ 3000 hours*

CATERPILLAR TRACKED EXCAVATORS

245D 7ZJ (1992-1993)



PUMP DRIVE

Capacity: 9 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 250 hours/ 1 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 250 hours/ 1 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 250 hours/ 1 months

SWING REDUCTION UNIT

Capacity: 44,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours

CATERPILLAR TRACKED EXCAVATORS

245D 7ZJ (1992-1993)



TRACK PINS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

TRACK ROLLERS & IDLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.