

CATERPILLAR TRACKED EXCAVATORS

320D RR SRT (2006-2011)



ENGINE 3066 ATAAC
Capacity: 30 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 500 hours/ 3 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Change every 500 hours/ 3 months

FINAL DRIVES
Capacity: 8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 250 hours/ 1 months

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 250 hours/ 1 months

CATERPILLAR TRACKED EXCAVATORS

320D RR SRT (2006-2011)



HYDRAULIC SYSTEM

Capacity: 165 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra*Change every 2000 hours/ 12 months*

USE	CLIMATE
50% use of breaker	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 1000 hours*

USE	CLIMATE
50% use of breaker	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra*Change every 1000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

CATERPILLAR TRACKED EXCAVATORS

320D RR SRT (2006-2011)



COOLING SYSTEM

Capacity: 1,5 liter (Reservoir), Capacity: 25 liter (System)

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 12000 hours/ 72 months

SWING GEAR

Capacity: 21,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12 months/ 2000 hours

SWING REDUCTION UNIT

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

TRACK IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

CATERPILLAR TRACKED EXCAVATORS

320D RR SRT (2006-2011)



TRACK ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.