

ENGINE 3412E Capacity: 83 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1 months/ 250 hours

HYDRAULIC SYSTEM Capacity: 891 liter (Hydraulic tank), Capacity: 1686 liter (System)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Multifleet SCD 30	Gear Oil Alcat 30			
Check every 10 hours, change every 24 months/ 4000 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30		
Check every 10 hours, change every	24 months/ 4000 hours			

USE CLIMATE
Biodegradable oil Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

Check every 10 hours, change every 24 months/ 4000 hours

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 113 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 7	months/ 12000 hours	

Check every 10 hours, change every 72 months/ 12000 hours



Capacity: 274 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 12 months/ 2000 hours		
SWING REDUCTION UNIT Capacity: 14 liter (each), Capacity: 38 liter	(Total system volume)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours/ 6 months		



USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Normal Wediterranean CLIMATE Moderate Moderate CLIMATE Moderate Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Moderate CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean USE Normal USE Normal Wediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal Wediterranean CLIMATE Moderate Moderate	TRACK IDLERS	
PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Mediterranean Mediterranean USE CLIMATE Moderate CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 40	USE	CLIMATE
Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean Mediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 40	Normal	Mediterranean
USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Moderate CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE Vormal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal Multifleet SCD 40 CLIMATE Moditerranean CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1	Multifleet SCD 40	
PRODUCT RECOMMENDATION 1 Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Normal Multifleet SCD 40	USE	CLIMATE
Multifleet SCD 30 TRACK ROLLERS USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Normal Multifleet SCD 40 USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1	Normal	Moderate
TRACK ROLLERS USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	
Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 USE Normal PRODUCT RECOMMENDATION 1	Multifleet SCD 30	
Normal Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 USE Normal PRODUCT RECOMMENDATION 1		
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 USE Normal PRODUCT RECOMMENDATION 1 Mediterranean CLIMATE Moderate	TRACK ROLLERS	
PRODUCT RECOMMENDATION 1 Multifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 CLIMATE Moderate	USE	CLIMATE
Wultifleet SCD 40 USE Normal PRODUCT RECOMMENDATION 1 CLIMATE Moderate	Normal	Mediterranean
USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	
Normal Moderate PRODUCT RECOMMENDATION 1	Multifleet SCD 40	
PRODUCT RECOMMENDATION 1	USE	CLIMATE
	Normal	Moderate
Multifleet SCD 30	PRODUCT RECOMMENDATION 1	
	Multifleet SCD 30	



TRAVEL REDUCTION UNIT Capacity: 22 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours/ 6 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.