## CATERPILLAR WHEELED LOADERS 990 II CATERPILLAR 3412 DITA (1999-2005)



ENGINE Caterpillar 3412 DITA			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
01 0501	·	·	

Change every 250 hours

DIFFERENTIAL FRONT + REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 500 hours, change eve	ery 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours, change eve	ery 2000 hours	

TRANSMISSION Powershift		
use Normal		сымате Mediterranean
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 500 hours, change eve	ery 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		

Check every 500 hours, change every 1000 hours

**Gear Oil Alcat 10W** 

HYDRAULIC SYSTEM			
use Normal		сымате Moderate	
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	
Check every 500 hours, change ever	y 2000 hours		

## CATERPILLAR WHEELED LOADERS 990 II CATERPILLAR 3412 DITA (1999-2005)



BUCKET LOWER PINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

BUCKET LOWER PINS OIL LUBRICATED			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

FINAL DRIVES FRONT + REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 500 hours, change every 2000 hours			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 500 hours, change every 2000 hours			

## CATERPILLAR WHEELED LOADERS 990 II CATERPILLAR 3412 DITA (1999-2005)



STEERING GEAR UNIT			
	CLIMATE		
	Moderate		
PRODUCT RECOMMENDATION 2			
Gear Oil Alcat 50			
	CLIMATE		
	Arctic		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.