

# CATERPILLAR LOAD HAUL DUMPERS

## R1300G SERIES 2 RSL (2004-2008)

**ENGINE**

Capacity: 15,5 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Check every 10 hours, change every 1 months/ 250 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 10W-40***Check every 10 hours, change every 1 months/ 250 hours***DIFFERENTIAL FRONT**

Capacity: 38 liter (+ hub reductions)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours***DIFFERENTIAL REAR**

Capacity: 42 liter (+ hub reductions)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR LOAD HAUL DUMPERS

## R1300G SERIES 2 RSL (2004-2008)



### HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

### HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

### TRANSMISSION Powershift

Capacity: 56 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30**

PRODUCT RECOMMENDATION 2

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR LOAD HAUL DUMPERS

## R1300G SERIES 2 RSL (2004-2008)



### HYDRAULIC SYSTEM

Capacity: 88 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Check every 10 hours, change every 2000 hours/ 12 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Check every 10 hours, change every 2000 hours/ 12 months*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Check every 10 hours, change every 2000 hours/ 12 months*

### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 43,9 liter

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 10 hours, change every 48 months/ 6000 hours*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 24 months/ 3000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.