

CATERPILLAR COMPACT TRACKED LOADERS 259D

FTK/FTL/GTK/CATERPILLAR C3,3B DIT



ENGINE C3.3B DIT Tier 4i
Capacity: 11,2 liter

USE	CLIMATE
Preferred, fuel sulfur level <0,05%	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Preferred, fuel sulfur level <0,05%	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Fuel sulfur level 0,5-1 %	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 6 months/ 250 hours

USE	CLIMATE
Fuel sulfur level 0,5-1 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 6 months/ 250 hours

USE	CLIMATE
Alternative, fuel sulfur level <0,05%	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Alternative, fuel sulfur level <0,05%	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Fuel sulfur level 0,05-0,5 %	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

CATERPILLAR COMPACT TRACKED LOADERS 259D

FTK/FTL/GTK/CATERPILLAR C3,3B DIT



(2013 AND AFTER)

USE		CLIMATE
Fuel sulfur level 0,05-0,5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		

HYDRAULIC SYSTEM		
Capacity: 39 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
<i>Check every 10 hours, change every 2000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agri diesel CRD+ 15W-40	Agri fluid HT-Plus	Kroontrak MTH 10W-30
<i>Check every 10 hours, change every 2000 hours</i>		

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Check every 10 hours, change every 2000 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CATERPILLAR COMPACT TRACKED LOADERS 259D

FTK/FTL/GTK/CATERPILLAR C3,3B DIT

**COOLING SYSTEM**

Capacity: 14 liter

USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

*Check every 10 hours, change every 36 months/ 3000 hours***TRACK IDLERS**

Capacity: 0,35 liter (dual flange), Capacity: 0,35 liter (single flange), Capacity: 0,23 liter (triple flange)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agirdiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

TRACK ROLLERS

Capacity: 0,24 liter (each)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agirdiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

TRAVEL REDUCTION UNIT

Capacity: 1 liter (each)

CATERPILLAR COMPACT TRACKED LOADERS 259D

FTK/FTL/GTK/CATERPILLAR C3,3B DIT



USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
<i>Check every 250 hours, change every 500 hours</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
<i>Change every 250 hours/ 6 months</i>		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Check every 250 hours, change every 500 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 250 hours, change every 500 hours</i>		
USE		CLIMATE
Initial service (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 250 hours/ 6 months</i>		
USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 250 hours/ 6 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.