## CATERPILLAR COMPACT TRACKED LOADERS 279C SERIES 2 KWB/CATERPILLAR C3.4 DIT (2011-2013)



ENGINE C3.4 DIT Capacity: 10 liter		
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2  Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3  Multifleet SHPD 15W-40
Check every 10 hours, change every	500 hours/ 12 months	1
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40	
Check every 10 hours, change every	500 hours/ 12 months	'

HYDRAULIC SYSTEM Capacity: 57 liter (Hydraulic system including tank), Capacity: 42 liter (Hydraulic tank)		
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours

Objects are set to be a set of the set of th		
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 10 hours, change every 2000 hours

USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

## CATERPILLAR COMPACT TRACKED LOADERS 279C SERIES 2 KWB/CATERPILLAR C3.4 DIT (2011-2013)



COOLING SYSTEM Capacity: 13,9 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72	nonths/ 12000 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 36 months/ 3000 hours

DRIVE CHAIN CASE Capacity: 10 liter (each)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 3 months/ 500 hours, ch	ange every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Check every 3 months/ 500 hours, ch	ange every 6 months/ 1000 hours	•

TRACK IDLERS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

## CATERPILLAR COMPACT TRACKED LOADERS 279C SERIES 2 KWB/CATERPILLAR C3.4 DIT (2011-2013)



	CLIMATE
Normal	
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 10W-40	
	Dieselfleet CD+ 15W-40  PRODUCT RECOMMENDATION 2

TRAVEL REDUCTION UNIT Capacity: 1 liter (each)	
USE	CLIMATE
Preferred	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
01 1 0501 1 5001	

Check every 250 hours, change every 500 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

Change every 250 hours/ 6 months

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 500 hours

USE		CLIMATE
Initial service (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 250 hours		

PRODUCT RECOMMENDATION

## CATERPILLAR COMPACT TRACKED LOADERS 279C SERIES 2 KWB/CATERPILLAR C3.4 DIT (2011-2013)



USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change ayeny 250 hours		

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.