PRODUCT RECOMMENDATION

CATERPILLAR COMPACT TRACKED LOADERS 289C CATERPILLAR C3.4 DIT (2008-2011)

ENGINE C3.4 DIT
Capacity: 10 liter

USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	**Dieselfleet MSP 15W-40**	
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	**Agrisynth MSP 10W-40**	**Armado Synth LSP Ultra 10W-40**
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Check every 10 hours, change every 500 hours/ 12 months		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	**Multifleet SHPD 10W-40**	
Check every 10 hours, change every 500 hours/ 12 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR COMPACT TRACKED LOADERS 289C CATERPILLAR C3.4 DIT (2008-2011)

HYDRAULIC SYSTEM
Capacity: 42 liter (Hydraulic tank), Capacity: 57 liter (System)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Check every 10 hours, change every 2000 hours/ 12 months		

COOLING SYSTEM
Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 12000 hours/ 72 months		

TRAVEL REDUCTION UNIT
Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
Check every 250 hours, change every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367