CATERPILLAR COMPACT TRACKED LOADERS 289C SERIES 2 RTD/CATERPILAR C3.4 DIT (2012 AND



ENGINE C3.4 DIT Capacity: 10 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every	500 hours/ 12 months		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40		

HYDRAULIC SYSTEM Capacity: 39 liter (Hydraulic tank)	
USE	CLIMATE Mediterranean
Normal	
Homia	Mediterranean
PRODUCT RECOMMENDATION 1	Mediterranean

Check every 10 hours, change every 2000 hours

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 2000 hours

USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

Coolant SP 15+

CATERPILLAR COMPACT TRACKED LOADERS 289C SERIES 2 RTD/CATERPILAR C3.4 DIT (2012 AND



Coolant -38 Organic NF

CCOLING CYSTEM Capacity: 13,9 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 m	nonths/ 12000 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Coolant SP 12

Check every 10 hours, change every 36 months/ 3000 hours

DRIVE CHAIN CASE Capacity: 10 liter (each)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 3 months/ 500 hours, ch	nange every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Check every 3 months/ 500 hours, ch	nange every 6 months/ 1000 hours	

USE		CLIMATE
Normal		Mediterranean
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
0.5		CLIMATE
SE .		
ose Normal		Moderate
	PRODUCT RECOMMENDATION 2	Moderate

CATERPILLAR COMPACT TRACKED LOADERS 289C SERIES 2 RTD/CATERPILAR C3.4 DIT (2012 AND



USE		climate Mediterranean	
Normal			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
JSE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40		

TRAVEL REDUCTION UNIT Capacity: 1 liter (each)	
USE	CLIMATE
Preferred	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Charles avenue 250 havens abanes avenue 500 h	<u>'</u>

Check every 250 hours, change every 500 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

Change every 250 hours/ 6 months

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 500 hours

Moderate	
0	
	0

Check every 250 hours, change every 500 hours

USE		CLIMATE
Initial service (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 250 hours		

PRODUCT RECOMMENDATION

CATERPILLAR COMPACT TRACKED LOADERS 289C SERIES 2 RTD/CATERPILAR C3.4 DIT (2012 AND



AFTER)		CLIMATE		
Initial service (alternative)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Change over 250 hours				

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.