

CATERPILLAR SKID STEER LOADERS

272C CATERPILLAR C3,4T (2007-2013)

**ENGINE 3044C DIT**

Capacity: 10 liter, Filter capacity: 1 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 250 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

*Check every 250 hours, change every 500 hours/ 12 months***HYDRAULIC SYSTEM HYDROSTATIC DRIVE**

Capacity: 57 liter (Hydraulic system including tank), Capacity: 42 liter (Hydraulic tank)

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR SKID STEER LOADERS

272C CATERPILLAR C3,4T (2007-2013)



USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

EXTERNAL GREASE POINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 13,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Change every 12000 hours/ 72 months</i>		

DRIVE CHAIN CASE Capacity: 11 liter		
USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 3 months/ 500 hours, change every 6 months/ 1000 hours</i>		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
<i>Check every 3 months/ 500 hours, change every 6 months/ 1000 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.