

CATERPILLAR MOTOR GRADERS 140G 3PL

(1973-1995)



ENGINE 3306
Capacity: 27 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Multifleet SCD 40 | Multifleet SCD 30 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Multifleet SCD 50 | Multifleet SCD 40 |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

CATERPILLAR MOTOR GRADERS 140G 3PL

(1973-1995)



TRANSMISSION Powershift

Capacity: 83 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 40 | Multifleet SCD 30 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|-------------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|-----------------------------|-----------------------------|-------------------------------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 30 liter (Tank)

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

COOLING SYSTEM

Capacity: 40 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR MOTOR GRADERS 140G 3PL (1973-1995)

**CIRCLE DRIVE UNIT**

Capacity: 7,6 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 50 | Multifleet SCD 40 | |

Change every 2000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

Change every 2000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

*Change every 2000 hours/ 12 months***TANDEM DRIVE UNIT**

Capacity: 64 liter (each side)

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 50 | Multifleet SCD 40 | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

CATERPILLAR MOTOR GRADERS 140G 3PL (1973-1995)


WHEEL SPINDLE HOUSINGS FRONT

Capacity: 3,8 liter (each side)

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 50 | Multifleet SCD 40 | |

Check every 3 months/ 500 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

Check every 3 months/ 500 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Check every 3 months/ 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.