CATERPILLAR MOTOR GRADERS 16M B9H (2006 AND AFTER)



ENGINE C13 Acert Capacity: 35 liter				
USE		CLIMATE		
Preferred		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 3 months/ 500 hours				
USE		CLIMATE		
Preferred		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40			
Check every 10 hours, change every 3 months/ 500 hours				
USE		CLIMATE		
Alternative (acceptable)		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40			
Check every 10 hours, change every 3 months/ 500 hours				
USE		CLIMATE		
Alternative (acceptable)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40		
Check every 10 hours, change every 3 months/ 500 hours				

TANDEM DRIVE

Capacity: 127,8 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE Capacity: 100,3 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gear Oil Alcat 30	Gear Oil Alcat 50			
Check every 10 hours, change every 6 months/ 1000 hours				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 10 hours, change every 6 months/ 1000 hours				

CATERPILLAR MOTOR GRADERS 16M B9H (2006 AND AFTER)



HYDRAULIC SYSTEM Capacity: 64 liter (Hydraulic tank)				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Gear Oil Alcat 30		
Check every 100 hours, change every 12 months/ 2000 hours				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT		
Check every 100 hours, change every 12 months/ 2000 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 100 hours, change every 12 months/ 2000 hours				

WHEEL SPINDLE BEARING FRONT Capacity: 0,8 liter (each wheel)				
USE Constitution (Constitution)		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 50				
Check every 3 months/ 500 hours, change every 24 months/ 2000 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				
Check every 3 months/ 500 hours, change every 24 months/ 2000 hours				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 3 months/ 500 hours, change every 24 months/ 2000 hours				

PRODUCT RECOMMENDATION

CATERPILLAR MOTOR GRADERS 16M B9H (2006 AND AFTER)



COOLING SYSTEM Capacity: 49 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 months/ 12000 hours		

CIRCLE DRIVE GEARBOX Capacity: 7,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.