

CATERPILLAR BACKHOE LOADERS 426B

5YJ, 6KL (1991-1996)

**ENGINE**

Capacity: 8,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

*Change every 250 hours***DIFFERENTIAL FRONT**

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

*Check every 500 hours, change every 2000 hours***DIFFERENTIAL FRONT POWERED AXLE**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 500 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 2000 hours

CATERPILLAR BACKHOE LOADERS 426B

5YJ, 6KL (1991-1996)



DIFFERENTIAL REAR

Capacity: 18,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 500 hours, change every 2000 hours

DIFFERENTIAL REAR STEERABLE AXLE

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 500 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 2000 hours

FINAL DRIVES FRONT POWERED AXLE

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 500 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 2000 hours

CATERPILLAR BACKHOE LOADERS 426B

5YJ, 6KL (1991-1996)



FINAL DRIVES REAR STEERABLE AXLE

Capacity: 8,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 500 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 2000 hours

TRANSMISSION + TORQUE CONVERTER

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Change every 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Change every 1000 hours

CATERPILLAR BACKHOE LOADERS 426B

5YJ, 6KL (1991-1996)



HYDRAULIC SYSTEM

Capacity: 37,9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 500 hours, change every 2000 hours*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 15,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

CATERPILLAR BACKHOE LOADERS 426B 5YJ, 6KL (1991-1996)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.