

SE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
Check every 10 hours, change every	3 months/ 500 hours	
use Preferred		climate Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	
Check every 10 hours, change every	3 months/ 500 hours	
use Alternative (acceptable)		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	
Check every 10 hours, change every	3 months/ 500 hours	
use Alternative (acceptable)		climate Moderate
PRODUCT RECOMMENDATION 1 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
Check every 10 hours, change every	3 months/ 500 hours	
use Acceptable		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
Check every 10 hours, change every	250 hours/ 3 months	
use Acceptable		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3



DIFFERENTIAL FRONT POWERED AXLE Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

DIFFERENTIAL REAR 133-7234 FRICTION DISC

Capacity: 24 liter, Capacity: 1 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR 230-4017 BRAKE DISCS

Capacity: 24 liter, Capacity: 0,15 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES FRONT POWERED AXLE Capacity: 0,7 liter (each side)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			



TRANSMISSION Powershift Capacity: 20 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 10 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 10 hours, change every 6 months/ 1000 hours			

TRANSMISSION + TORQUE CONVERTER Capacity: 19 liter (2WD), Capacity: 20,5 liter (4WD)		
USE	3,0	CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every	6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 6 months/ 1000 hours



Capacity: 49 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change eve	ry 2000 hours/ 12 months	·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Agridiesel CRD+ 15W-40	Agrifluid HT-Plus
Check every 10 hours, change eve	ry 2000 hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change eve	ry 2000 hours/ 12 months	'

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Coolant SP 17	COOLING SYSTEM Capacity: 23,6-25,5 liter	
PRODUCT RECOMMENDATION 1	USE	
	Normal	Moderate
Coolant SP 17	PRODUCT RECOMMENDATION 1	
	Coolant SP 17	

Check every 10 hours, change every 36 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.