

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH460B SLF900-> (2003 AND AFTER)



**ENGINE** 3054E ATAAC  
Capacity: 8,4 liter

| USE                | CLIMATE       |
|--------------------|---------------|
| Normal (preferred) | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |
|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 6 months*

| USE                      | CLIMATE       |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 6 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-----------------------------|-----------------------------|-----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Check every 10 hours, change every 500 hours/ 6 months*

### DIFFERENTIAL FRONT

Capacity: 14 liter, Capacity: 0,45 liter (Friction modifier)

We are unable to give a standard recommendation for this component. Please contact our service department.

### DIFFERENTIAL REAR

Capacity: 14 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 30</b> |  |  |

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gear Oil Alcat 10W</b> |  |  |

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH460B SLF900-> (2003 AND AFTER)



### HUB REDUCTIONS FRONT

Capacity: 1,7 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

### HUB REDUCTIONS REAR

Capacity: 1,7 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

### HYDRAULIC SYSTEM

Capacity: 91 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

Check every 10 hours, change every 1000 hours/ 12 months

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

Check every 10 hours, change every 1000 hours/ 12 months

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH460B SLF900-> (2003 AND AFTER)



### GREASE POINTS/NIPPLES

| USE                            |                          | CLIMATE  |
|--------------------------------|--------------------------|----------|
| Normal                         |                          | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 |          |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     |          |

### COOLING SYSTEM

Capacity: 22,5-24,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

Check every 10 hours, change every 72 months/ 12000 hours

### SERVICE BRAKE SYSTEM

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.