## **CATERPILLAR FELLER BUNCHERS 543 ASJ**



ENGINE 3126 Capacity: 31 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE			
Normal	Mediterranean			
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 50				
Check every 50 hours, change every 12 months/ 2000 hours				
JSE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				
Check every 50 hours, change every 12 months/ 2000 hour	'S			
USE	CLIMATE			
Normal	Arctic			
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				

## **CATERPILLAR FELLER BUNCHERS 543 ASJ**



DIFFERENTIAL REAR Capacity: 52 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 50				
Check every 500 hours, change every 12	months/ 2000 hours			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				
Check every 500 hours, change every 12 months/ 2000 hours				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 500 hours, change every 12 months/ 2000 hours				

# **TRANSMISSION** Capacity: 3,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM Capacity: 300 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gear Oil Alcat 10W	Gear Oil Alcat 30			

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM Capacity: 45 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 17			
Check every 10 hours, change every 72 months/ 12000 hours			

#### PRODUCT RECOMMENDATION

## **CATERPILLAR FELLER BUNCHERS 543 ASJ**



PUMP DRIVE Capacity: 3,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.