PRODUCT RECOMMENDATION

# CATERPILLAR FELLER BUNCHERS 552

**ENGINE** C9 Acert
Capacity: 39 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 10 hours, change every 1 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrisynth LSP 10W-40** | **Multifleet SHPD 10W-40** | |

*Check every 10 hours, change every 1 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agridiesel CRD+ 15W-40** | **Multifleet SHPD 15W-40** | |

*Check every 10 hours, change every 1 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 10W-40** |

*Check every 10 hours, change every 1 months/ 250 hours*

**HYDRAULIC HOOD TILT SYSTEM**
Capacity: 3,8 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 30** | | |

*Check every 10 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 10 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR FELLER BUNCHERS 552

## HYDRAULIC SYSTEM
Capacity: 318 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 30** | | |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 10 hours, change every 6 months/ 1000 hours*

## HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN
Capacity: 0,65-1,22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM
Capacity: 36 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Coolant SP 17** | | |

*Check every 10 hours, change every 72 months/ 12000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR FELLER BUNCHERS 552

## SWING REDUCTION UNIT
Capacity: 10 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Change every 250 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |
| *Change every 250 hours* | | |

## TRAVEL REDUCTION UNIT
Capacity: 6 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367