

PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40
Normal		Moderate
USE		CLIMATE
ENGINE C7 Acert Capacity: 17 liter		

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL FRONT Capacity: 52 liter USE Normal Nediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 50 hours, change every 12 months/2000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/2000 hours USE Normal Check every 50 hours, change every 12 months/2000 hours USE Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/2000 hours USE CLIMATE Arctic Mediterranean Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean	Check every 10 hours, change every 1 months/ 250 hour	'S
Capacity: 52 liter USE Normal Normal Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Check every 50 hours, change every 12 months/ 2000 hours USE Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 1		
Normal Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic CLIMATE Arctic CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean Mediterranean		
Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Normal Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Moderate Moderate	<u> </u>	CI IMATE
Gear Oil Alcat 50 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Mediterranean Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean		
Check every 50 hours, change every 12 months/ 2000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean	PRODUCT RECOMMENDATION 1	
CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1	Gear Oil Alcat 50	
Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean Moderate PRODUCT RECOMMENDATION 1	Check every 50 hours, change every 12 months/ 2000 ho	purs
Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Mediterranean CHECK EVERY 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1	USE	CLIMATE
Gear Oil Alcat 30 Check every 50 hours, change every 12 months/ 2000 hours USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Moderate Fluid analysis Moderate	Normal	Moderate
Check every 50 hours, change every 12 months/ 2000 hours USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Moderate Fluid analysis Moderate	PRODUCT RECOMMENDATION 1	
USE Normal Normal Arctic PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE CLIMATE Fluid analysis Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean	Gear Oil Alcat 30	
Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis Mediterranean PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean Check every 500 hours USE CLIMATE Moderate Fluid analysis Moderate	Check every 50 hours, change every 12 months/ 2000 ho	ours
Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Mediterranean CLIMATE Moderate Fluid analysis Moderate	USE	CLIMATE
Gear Oil Alcat 10W Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Mediterranean CLIMATE LIMATE Moderate PRODUCT RECOMMENDATION 1	Normal	Arctic
Check every 50 hours, change every 12 months/ 2000 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE Fluid analysis CLIMATE Mediterranean CLIMATE Moderate PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	
CLIMATE Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE CLIMATE CLIMATE CLIMATE Moderate PRODUCT RECOMMENDATION 1	Gear Oil Alcat 10W	
Fluid analysis PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50 Check every 500 hours USE Fluid analysis CLIMATE Moderate PRODUCT RECOMMENDATION 1	Check every 50 hours, change every 12 months/ 2000 ho	ours
Gear Oil Alcat 50 Check every 500 hours USE Fluid analysis PRODUCT RECOMMENDATION 1 CLIMATE Moderate	USE	CLIMATE
Gear Oil Alcat 50 Check every 500 hours USE CLIMATE Fluid analysis PRODUCT RECOMMENDATION 1	Fluid analysis	Mediterranean
Check every 500 hours USE CLIMATE Fluid analysis PRODUCT RECOMMENDATION 1		
CLIMATE Fluid analysis Moderate PRODUCT RECOMMENDATION 1	Gear Oil Alcat 50	
Fluid analysis Moderate PRODUCT RECOMMENDATION 1	Check every 500 hours	
PRODUCT RECOMMENDATION 1	USE	CLIMATE
	Fluid analysis	Moderate
Gear Oil Alcat 30		
	Gear Oil Alcat 30	



USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours		
DIFFERENTIAL REAR Capacity: 52 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 50 hours, change every 12 m	onths/ 2000 hours	
USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 500 hours		
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 500 hours		
USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours		



TRANSMISSION Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 10 hours, change every 3	B months/ 500 hours	
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 1 months/ 250 hours		

HYDRAULIC SYSTEM Capacity: 227 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	MoS2 Grease EP 2

COOLING SYSTEM Capacity: 45 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Check every 10 hours, change every 72 mo.	ths/ 12000 hours



PUMP DRIVE Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 10 hours, change ever	y 2000 hours/ 12 months	
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.