

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-534B 5RN



**ENGINE** Caterpillar  
Capacity: 7,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Multifleet SCD 40</b>	<b>Multifleet SCD 30</b>

*Check every 10 hours, change every 250 hours/ 3 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Check every 10 hours, change every 250 hours/ 3 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 10W</b>	

*Check every 10 hours, change every 250 hours/ 3 months*

**PLANETARY GEARS**  
Capacity: 1 liter (each)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>

*Check every 50 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Check every 50 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>

*Check every 50 hours, change every 1000 hours/ 12 months*

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-534B 5RN



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Change every 250 hours/ 6 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Change every 250 hours/ 6 months*

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>	

*Change every 250 hours/ 6 months*

### HYDRAULIC SYSTEM

Capacity: 59 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Check every 10 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-534B 5RN



### COOLING SYSTEM

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 10 hours, change every 2000 hours/ 24 months*

### VIBRATORY BEARING UNIT

Capacity: 11 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Abacot MEP Synth 220</b>	<b>Abacot MEP 220</b>	

*Check every 50 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*