CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CD54 J5R (2009-2012)



ENGINE 3054C T Capacity: 9 liter		
USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40	Dieselfleet CD+ 15W-40
Check every 6 months/ 500 hours		·
USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40
Check every 6 months/ 500 hours		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 500	hours/ 6 months	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40
Check every 10 hours, change every 500	hours/ 6 months	,

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change ever	y 6 months/ 1000 hours	
JSE		CLIMATE
		Moderate
Fluid analysis, alternative		Moderate
Fluid analysis, alternative	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CD54 J5R (2009-2012)



COOLING SYSTEM Capacity: 15-19 liter		
USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 12 months, change every 72	months/ 12000 hours	
USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 6 months/ 500 hours		

ECCENTRIC WEIGHT HOUSING Capacity: 7,3 liter (each)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP HD 220	
Check every 100 hours, change eve	urs/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo