

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CP-563C 5JN00612 ->

### (1995-2000)



**ENGINE** 3116T  
Capacity: 20 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 250 hours/ 3 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Check every 10 hours, change every 250 hours/ 3 months*

**TRANSAXLE**  
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 110 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 1000 hours/ 12 months*

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CP-563C 5JN00612 ->

### (1995-2000)



#### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease**

PRODUCT RECOMMENDATION 2

**Labora Grease**

#### COOLING SYSTEM

Capacity: 33,1 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Check every 10 hours, change every 72 months/ 6000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 24 months/ 3000 hours*

#### DRUM COOLING

Capacity: 22,5 liter

USE	CLIMATE
At overhauls only	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

PRODUCT RECOMMENDATION 2

**Gear Oil Alcat 30**

USE	CLIMATE
At overhauls only	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30**

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CP-563C 5JN00612 ->

### (1995-2000)

**ECCENTRIC WEIGHT HOUSING**

Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Abacot MEP HD 220**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

**FINAL DRIVE - DRUM**

Capacity: 3,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Abacot MEP Synth 220**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

**VIBRATORY SUPPORT**

Capacity: 0,85 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Gearlube HS GL-5 80W-140**

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.