# CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-76 C7L/JCP (2006 AND



AFTER)

ENGINE C6.6 Acert Capacity: 16,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 500 hours/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 500 hours/ 6 months		

#### **DIFFERENTIAL**

Capacity: 17 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS Capacity: 3,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 3 months/ 250 hours, change	Check every 3 months/ 250 hours, change every 12 months/ 1000 hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours		
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Change every 250 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Change every 250 hours			

PRODUCT RECOMMENDATION 1

Helar 0W-40

### **CATERPILLAR VIBRATORY COMPACTORS** CB/CC/CD/CP/CS CP-76 C7L/JCP (2006 AND



PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

AFTER)

HYDRAULIC SYSTEM Capacity: 90 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every 2000 hours/ 12 months		
USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

USE	CLIMATE
Nigorous	
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 10 hours, change every 72 months/ 12000 hours

USE		CLIMATE
illed for life		Mediterranean
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
SE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
lelar 0W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

## CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CP-76 C7L/JCP (2006 AND



AFTER)

ECCENTRIC WEIGHT HOUSING Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Change every 36 months/ 3000 hours		
FINAL DRIVE - DRUM Capacity: 4,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 250 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		
Change every 250 hours		

PRODUCT RECOMMENDATION

### **CATERPILLAR VIBRATORY COMPACTORS** CB/CC/CD/CP/CS CP-76 C7L/JCP (2006 AND



AFTER)

Capacity: 0,95 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		
Check every 3 months/ 250 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 250 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		
Change every 250 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.