DENKA LIFT BOOM LIFTS DK DK7 JR12 ECO



| HYDRAULIC SYSTEM Capacity: 42 liter (Hydraulic tank), Capacity: 65 liter (System) | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 22 | | |
| Check every 2 weeks, change every 24 months | | |

every 2 weeks, change every 24 mont

| GREASE POINTS/NIPPLES OTHERS | | |
|------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 2 weeks

| GREASE POINTS/NIPPLES SWING GEAR | | |
|----------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |
| Change every 12 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.