DIECI TELESCOPIC HANDLERS AGRI FARMER 30.7 IVECO NEF F4GE0454A



ENGINE Iveco NEF F4GE0454A Capacity: 10 liter (Dry fill), Capacity: 9,5 lit	er (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 7,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 6 months/ 500 hours, ch	ange every 12 months/ 1000 hours	'

DIFFERENTIAL REAR Capacity: 7,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 6 months/ 500 hours, ch	ange every 12 months/ 1000 hours	

GEARBOX Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 6 months/ 500 hours, ch	ange every 12 months/ 1000 hours	

HUB REDUCTIONS FRONT Capacity: 1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 6 months/ 500 hours, ch	ange every 12 months/ 1000 hours	·

DIECI TELESCOPIC HANDLERS AGRI FARMER 30.7 IVECO NEF F4GE0454A



HUB REDUCTIONS REAR Capacity: 1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM HYDROSTA Capacity: 105 liter (Service fill), Cap	ATIC DRIVE pacity: 155 liter (Total system volume)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Check every 10 hours, change eve	ry 500 hours/ 6 months	·	

HYDRAULIC BRAKE SYSTEM Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 100 hours, change every 2	oours/ 24 months

GREASE POINTS/NIPPLES Capacity: 5,5 kg		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Chock overy 10 hours, change over	v 2000 hours/24 months	

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

DIECI TELESCOPIC HANDLERS AGRI FARMER 30.7 IVECO NEF F4GE0454A



information contained herein is subject to changes without notification.