DIECI TELESCOPIC HANDLERS AGRI MAX 45.8 TA IVECO NEF F4GE0484C



ENGINE Iveco NEF F4GE0484C Capacity: 10 liter (Dry fill), Capacity: 9,5 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 7,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

DIFFERENTIAL REAR Capacity: 7,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

GEARBOX Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

HUB REDUCTIONS FRONT Capacity: 1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

DIECI TELESCOPIC HANDLERS AGRI MAX 45.8 TA IVECO NEF F4GE0484C



HUB REDUCTIONS REAR Capacity: 1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM HYDROSTATIC DRIVE Capacity: 105 liter (Service fill), Capacity: 155 liter (Total system volume)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

Check every 10 hours, change every 500 hours/ 6 months

HYDRAULIC BRAKE SYSTEM Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
	0 1	

Check every 100 hours, change every 2000 hours/24 months

GREASE POINTS/NIPPLES Capacity: 5,5 kg		
use Normal		сымате Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V. Postbus 149 7600 AC Almelo

DIECI TELESCOPIC HANDLERS AGRI MAX 45.8 TA IVECO NEF F4GE0484C



information contained herein is subject to changes without notification.