## DITCH WITCH MINI SKID STEER SK R230 KOHLER CH23S



ENGINE Kohler CH23S Capacity: 1,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		
Check every 10 hours, change every 100	hours		
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Check every 10 hours, change every 100	hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		
Change every 20 hours			
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 20 hours			
HYDRAULIC SYSTEM Capacity: 32.2 liter (Hydraulic system inclu	uding tonk) Consoits: 20.1 liter (Usedrau	lie tenk)	
Cabacity, 32.2 liter trivulaulic system incl	und lank). Cabacily, 29.1 nilel (nyulau		

Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Normal		Moderate		
USE		CLIMATE		

Check every 10 hours, change every 250 hours

GREASE POINTS/NIPPLES TRENCHER				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Labora Grease				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.