

# DITCH WITCH DIRECTIONAL DRILLS HT/JT

## JT2020 MACH 1 CUMMINS B3.3TAA, EPA

### TIER 3, EU STAGE IIIA



**ENGINE** Cummins B3.3TAA  
Capacity: 8 liter

**USE**

Normal, fuel sulfur level &lt;15 ppm

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra 10W-40**

## PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

## PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Check every 10 hours, change every 250 hours*

**GROUND DRIVE GEARBOX****USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**

Capacity: 72 liter (Hydraulic tank)

**USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

## PRODUCT RECOMMENDATION 2

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 3

**Agrifluid HT-Plus**

*Check every 10 hours, change every 500 hours*

**COOLING SYSTEM**

Capacity: 17 liter

**USE**

Normal

**CLIMATE**

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12**

## PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

*Check every 10 hours, change every 2000 hours/ 24 months*

**DRILLING FLUID PUMP**

We are unable to give a standard recommendation for this component. Please contact our service department.

# DITCH WITCH DIRECTIONAL DRILLS HT/JT JT2020 MACH 1 CUMMINS B3.3TAA, EPA TIER 3, EU STAGE IIIA



## ROTATION GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 50 hours, change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*