

DITCH WITCH ZAHN SERIES R150/230/300

R150 HONDA IGX440



ENGINE iGX440
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 10 hours, change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Change every 20 hours

HYDRAULIC SYSTEM

Capacity: 32,2 liter (Hydraulic system including tank), Capacity: 29,1 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 10 hours, change every 250 hours

GREASE POINTS/NIPPLES TRENCHER

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Labora Grease		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.