## DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D60S-2 DHIM DB58 (1999-2003)



ENGINE Daewoo DB58 Capacity: 14,5 liter USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **PRODUCT RECOMMENDATION 3** Agridiesel MSP 15W-40 Agridiesel CRD+ 15W-40 Dieselfleet CD+ 15W-40 Check every 10 hours, change every 1 months/ 250 hours USE CLIMATE Initial service Moderate PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

## Agridiesel MSP 15W-40Agridiesel CRD+ 15W-40Dieselfleet CD+ 15W-40

Change every 50 hours/ 1 week

| DRIVE AXLE (SHOE BRAKE)<br>Capacity: 11,8 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                            | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1500 hours                         | · · · ·                     |          |
| USE   |                             | CLIMATE  |
| Initial service                                 |                             | Moderate |

| Initial service          |                             | Moderate |
|--------------------------|-----------------------------|----------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
|                          |                             |          |

Change every 50 hours

| DRIVE AXLE (WET BRAKE)<br>Capacity: 14 liter |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal                                       |                          | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |
| Agrifluid HT-Plus                            | Agrifluid HT             |          |

```
Change every 1500 hours
```

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Initial service          |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Agrifluid HT-Plus        | Agrifluid HT             |          |
| Change every 50 hours    |                          | I        |

KROON-OIL B.V. Postbus 149 7600 AC Almelo

## DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D60S-2 DHIM DB58 (1999-2003)



| TRANSMISSION Powershift<br>Capacity: 17 liter |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 2032                                 | ATF Almirol              |          |
| Change every 1000 hours                       |                          |          |
| USE   |                          | CLIMATE  |
| Initial service                               |                          | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 2032                                 | ATF Almirol              |          |
| Change avery 50 hours                         |                          |          |

Change every 50 hours

## DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D60S-2 DHIM DB58 (1999-2003)



| BRAKE SYSTEM WET BRAKES<br>Capacity: 1 liter |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal                                       |                          | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |
| Perlus H 32                                  | Perlus AF 32             |          |
|  |                          |          |

Change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.