DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D70S-5 (3-SPEED) HYUNDAI D439E (2009 AND AFTER)



| ENGINE Hyundai D439E Capacity: 8,5 liter | | |
|-------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |
| Okaska wara 40 kawasa kawasa wara | | Diesemeet CD+ 13W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Change every 100 hours

| DRIVE AXLE (SHOE BRAKE) Capacity: 11,3 liter | | |
|----------------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 1 months/ 250 hours, change every 3 months/ 500 hours

| 01 1001 | | |
|--------------------------|-----------------------------|----------|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Initial service | | Moderate |
| USE | | CLIMATE |

Change every 100 hours

| | CLIMATE |
|-----------------------------|---------------------------------------------------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | |
| e every 3 months/ 500 hours | |
| | CLIMATE |
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT | |
| • | |
| | Agrifluid HT e every 3 months/ 500 hours PRODUCT RECOMMENDATION 2 |

DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D70S-5 (3-SPEED) HYUNDAI D439E (2009 AND AFTER)



| TRANSMISSION POWERSHIFT ZF 3W Capacity: 23 liter | G116 3/3 | |
|------------------------------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Check every 10 hours, change every 6 m | onths/ 1000 hours | • |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Check every 10 hours, change every 6 m | onths/ 1000 hours | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Change every 100 hours | | |
| | | |
| HYDRAULIC SYSTEM POWER STEERI Capacity: 117 liter | NG | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |

| Check every 1 | months/250 k | hours shange | 01/05/6 | montha/ | 1000 hours |
|---------------|-------------------|----------------|---------|---------|------------|
| CHECK EVERV I | 111011ti1S/ 230 I | iours, charine | CVC/VO | months/ | TOUU HOURS |

Perlus H 68

| | _ , , , | |
|--------------------------|--------------------------|----------|
| Perlus H 32 | Perlus H 22 | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Normal | | Moderate |
| USE | | CLIMATE |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

Perlus H 46

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D70S-5 (3-SPEED) HYUNDAI D439E (2009 AND AFTER)



| BRAKE SYSTEM WET BRAKES Capacity: 0,6 liter | | | |
|------------------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus H 32 | Perlus AF 32 | | |
| Check every 1 months/ 250 hours | · | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.