

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, ELECTRIC B/BC/BR B32S-5 (2005 AND AFTER)



## DRIVE AXLE (WET BRAKE)

Capacity: 9,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT***Change every 500 hours/ 3 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT***Change every 100 hours*

## HYDRAULIC SYSTEM POWER STEERING

Capacity: 32 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68***Change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32**

PRODUCT RECOMMENDATION 2

**Perlus H 22***Change every 2000 hours/ 12 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, ELECTRIC B/BC/BR B32S-5 (2005 AND AFTER)



## BRAKE SYSTEM WET BRAKES

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Perlus H 15**

*Check every 1 months/ 250 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*