PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G15S-5 MITSUBISHI G420F(E) (2007 AND AFTER)

## ENGINE Mitsubishi G420
Capacity: 4,2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Asyntho 5W-30** | **Synfleet SHPD 10W-40** | **Dieselfleet MSP 10W-30** |

*Check every 10 hours, change every 1 months/ 250 hours*

## DRIVE AXLE (SHOE BRAKE)
Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 1 months/ 250 hours, change every 9 months/ 1500 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 100 hours*

## DRIVE AXLE (WET BRAKE)
Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrifluid HT-Plus** | **Agrifluid HT** | |

*Check every 1 months/ 250 hours, change every 9 months/ 1500 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Agrifluid HT-Plus** | **Agrifluid HT** | |

*Change every 100 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G15S-5 MITSUBISHI G420F(E) (2007 AND AFTER)

## TRANSMISSION Powershift
Capacity: 10 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Change every 100 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Change every 100 hours*

## HYDRAULIC SYSTEM POWER STEERING
Capacity: 30 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus H 46** | **Perlus H 68** | |

*Check every 1 months/ 250 hours, change every 15 months/ 2500 hours*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus H 32** | **Perlus H 22** | |

*Check every 1 months/ 250 hours, change every 15 months/ 2500 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G15S-5 MITSUBISHI G420F(E) (2007 AND AFTER)

## BRAKE SYSTEM (SHOE BRAKE)
Capacity: 1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | **Drauliquid DOT 3** |

*Check every 1 months/ 250 hours*

## BRAKE SYSTEM WET BRAKES
Capacity: 1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Perlus H 15** | | |

*Check every 1 months/ 250 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367