PRODUCT RECOMMENDATION 1

Check every 10 hours, change every 1 months/ 250 hours

Asyntho 5W-30

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G30P-5 MITSUBISHI G424F (2007 AND AFTER)



ENGINE Mitsubishi G424F Capacity: 4,5-4,6 liter, Filter capacity: 0,3 l	iter	
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Check every 10 hours, change every 1 mg	onths/ 250 hours	
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 1 mg	onths/ 250 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G30P-5 MITSUBISHI G424F (2007 AND AFTER)



DIFFERENTIAL FRONT Capacity: 9,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 1 months/ 250 hours, change	every 3 months/ 500 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 1 months/ 250 hours, change	every 3 months/ 500 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 1 week/ 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 1 week/ 100 hours		

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G30P-5 MITSUBISHI G424F (2007 AND AFTER)



TRANSMISSION Powershift Capacity: 13 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 100 hours		
HYDRAULIC SYSTEM Capacity: 34 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Check every 1	months/ 250	hours, change	e every 15 n	nonths/ 2500	hours
USE					

Normal CLIMATE

Moderate

Perlus H 68

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
Perlus H 32 Perlus H 22

Check every 1 months/ 250 hours, change every 15 months/ 2500 hours

Perlus H 46

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX G30P-5 MITSUBISHI G424F (2007 AND AFTER)



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Check every 1 months/ 250 hours	

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ry 2000 hours/ 12 months	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.