DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC20SC-5 MITSUBISHI G420F(E) (2007 AND AFTER)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 1 months/ 250 hours, change every 9 n	nonths/ 1500 hours
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Check every 1 months/ 250 hours, change every 9 n	nonths/ 1500 hours
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 100 hours	
USE	CLIMATE
Initial service	Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC20SC-5 MITSUBISHI G420F(E) (2007 AND AFTER)



Capacity: 10 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 100 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 100 hours		
HYDRAULIC SYSTEM POWER STEERIN	NG	
Capacity: 30 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Check every 1 months/ 250 hours, change	e every 15 months/ 2500 hours	

PRODUCT RECOMMENDATION 2

Perlus H 22

Check every 1 months/ 250 hours, change every 15 months/ 2500 hours

USE

Normal

Perlus H 32

PRODUCT RECOMMENDATION 1

climate Moderate PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC20SC-5 MITSUBISHI G420F(E) (2007 AND AFTER)



BRAKE SYSTEM WET BRAKES Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 15	
Check every 1 months/ 250 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.