PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)

ENGINE Mitsubishi G430
Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		

Change every 50 hours/ 1 week

DRIVE AXLE (WET BRAKE)
Capacity: 9,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 1000 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 50 hours

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)

TRANSMISSION Powershift
Capacity: 13 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 1000 hours		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 1000 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 50 hours/ 1 week		

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours/ 1 week		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, LPG/PETROL G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)

HYDRAULIC SYSTEM POWER STEERING
Capacity: 34 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 46	**Perlus H 68**	
Change every 1000 hours		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 1000 hours		
USE		**CLIMATE**
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 46	**Perlus H 68**	
Change every 50 hours		
USE		**CLIMATE**
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367