

DOOSAN (DAEWOO) WHEELED EXCAVATORS DX-W DX170W DOOSAN DL06 (2008-2014)



ENGINE Doosan DL06
Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Change every 10 hours

DIFFERENTIAL FRONT
Capacity: 10,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 14 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

DOOSAN (DAEWOO) WHEELED EXCAVATORS DX-W DX170W DOOSAN DL06 (2008-2014)



HUB REDUCTIONS FRONT

Capacity: 2,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1000 hours*

HUB REDUCTIONS REAR

Capacity: 0,66 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 1000 hours*

TRANSMISSION

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

DOOSAN (DAEWOO) WHEELED EXCAVATORS DX-W DX170W DOOSAN DL06 (2008-2014)

**HYDRAULIC SYSTEM**

Capacity: 102 liter (Hydraulic tank), Capacity: 180 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

*Change every 1000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Change every 2000 hours***SWING REDUCTION UNIT**

Capacity: 2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) WHEELED EXCAVATORS DX-W DX170W DOOSAN DL06 (2008-2014)



information contained herein is subject to changes without notification.